

Claims

We claim:

1. A method for efficiently handling high contention locking in a multiprocessor computer system, comprising:
 - 5 organizing at least some of the processors into a hierarchy;
 - providing a lock selected from the group consisting of: an interruptible lock, and a lock which waits using only local memory; and
 - processing the lock responsive to the hierarchy.
- 10 2. The method of claim 1, wherein the processing step conditionally acquires the lock.
3. The method of claim 2, wherein the processing step returns a failure to grant the lock if the lock is not immediately available.
4. The method of claim 1, wherein the processing step unconditionally acquires the lock.
- 15 5. The method of claim 4, wherein the processing step spins on the lock until the lock is available.
6. The method of claim 4, further comprising allowing system interrupts while spinning on the lock
7. The method of claim 1, wherein the processing step unconditionally releases the lock.
- 20 8. The method of claim 1, wherein the processing step the processors spin on private memory.
9. The method of claim 1, wherein the hierarchy includes a data structure having a bit mask indicating which processors of a group are waiting for the lock.
- 25 10. The method of claim 1, wherein the hierarchy includes a data structure having a bit mask indicating which groups of processors have processors waiting for the lock.

- 25

22. An article comprising:
a computer-readable signal bearing medium;
means in the medium for hierarchically organizing at least some of the processors
of a computer system;
- 5 means in the medium for providing a lock selected from the group consisting of:
an interruptible lock, and a lock which waits using only local memory; and
means in the medium for processing the lock responsive to the hierarchy.
23. The article of claim 22, wherein the medium is a recordable data storage medium.
24. The article of claim 22, wherein the medium is a modulated carrier signal.
- 10 25. The article of claim 22, wherein the means is a conditional lock acquisition
primitive.
26. The article of claim 25, wherein a lock failure is indicated if the lock is not
immediately
available.
- 15 27. The article of claim 22, wherein the means is an unconditional lock acquisition
primitive.
28. The article of claim 28, wherein a spin stage is entered by a processor if the lock
is not
immediately available.
- 20 29. The article of claim 22, wherein the means is an unconditional lock release
primitive.
30. The article of claim 22, wherein said means is a release flag responsive to races
between acquisition and release of a lock.
- 25 31. The article of claim 22, wherein said means is a handoff flag responsive to a
processor requesting an unconditional lock from a processor requesting a
conditional lock.